



**ZONE 1
CL I/DIV 1**



**Remote Speaker
Microphone**



Push to Talk



ISM interface

IS-RSMG2.1

The lightweight IS-RSMG2.1 remote speaker microphone is specially designed for PTT applications. With its robust housing and safe ISM interface, it is an ideal addition to our mobile devices IS330.1 and IS530.1.

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.



< IS-RSMG2.1 >



ATEX approval: EX-Zone 1
Ⓜ II 2G Ex ib IIC T4 Gb



IECEx approval: EX-Zone 1
Ex ib IIC T4 Gb



NEC500 approval:
Class I/Division 1 Groups A B C D
Intrinsically Safe

TECHNICAL FEATURES

Loudspeaker	Dynamic 3-stage volume control Sensitivity: 93dB (1mW) Bandwidth: 50Hz ... 8kHz
Microphone	Electret Omni-Directional Sensitivity: -38dB ± 3dB (1kHz) Bandwidth: 50Hz ... 16kHz
Measurement	Size: 98,11 x 65,93 x 26,96 mm Weight: 212 g
Power supply	Over the connected device
Cable length	flexible spiral cable from 48 to 130 cm
Connection	ISM interface
Protection class	IP54 Operation range from -20 °C up to 60 °C

› i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. All other trademarks and copyrights are the properties of their respective owners. › © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | X180MD02REV02_EN_07.2021