

MICA



**BRIGHT TOOLS FOR
PROFESSIONALS.**

MICA® ML-808 

- HIGH-POWER CREE LED • TWO-MODE BEAM, 25 AND 100 LUMENS • OPERATING TIME UP TO 15 HOURS • RECHARGE IN LESS THAN 3 HOURS
- LED-BAR INDICATOR FOR BATTERY CAPACITY
- OPTIONAL EMERGENCY FUNCTION (EM) • OPTIONAL BLINKING FUNCTION (BK)




The MICA® ML-808 is the latest in high-powered ATEX hand lamps. It is a step up from the well-known MICA® ML-800. The new ML-808 is stored and recharged in the same MICA® MLC charging dock as previous MICA® ML-series lights. Two power modes allows the user to obtain the best combination of light power and usage time.

The lamp is equipped with an environmentally friendly NiMH battery offering continuous operating time up to 15 hours. Advanced electronics in the ML-808 protect the battery from deep discharges and warn the user of low battery charge by flashing the light beam when there is only 20 minutes of operating time left. The shock resistant IP-65 casing is manufactured entirely of anti-static plastic and aluminium. The lens is three millimetres thick and specially toughened. MICA® ML-808 is supplied with a strong belt clip and wrist strap.

TECHNICAL DATA	ML-808
Certification	II 2 G Ex ib op is IIC T4 Gb II 2 D Ex ib op is IIC T135°C Db
Area of classification: Gas	Zones 1 and 2
Area or classification: Dust	Zones 21 and 22
IP rating	IP65
Light source	Ultra-bright LED
Battery	6V NiMH
Operating time	Full power 4 hrs 30 min Low power 15 hrs
Operating temperature	-20 to +40 °C
Dimensions/Weight	120 x 64 x 55mm/400g




Intelligent chargers for MICA® lamps




MICA ILC4-VAC (FOR IL-SERIES)

Input: 85...265VAC




MICA ILC4

Input: 12...24VDC



MICA MLC (FOR ML-SERIES)



MICA IL-2

Rugged aluminium construction

LED light indicates charging state

LED light indicates charging state

LED indicators for charging state

Fast charge in less than 3 hours

Input voltage 90...265VAC

Supports ILC4 and MLC

EUR, US, SAA & UK plugs available