

L-90

Right angle torch

Light, small and easy to operate. It incorporates our famous LED Engine optic, including 2 LEDs (spot, flood and step light options). It easily adapts to the firefighter's tunic.



- LedEngine optic with 2 LEDs
- **Spot, flood and stroboscopic** options
- Step Lighting System : a light beam projected directly into the ground to illuminate the path
- BOOSTER function for high penetration
- High and low intensity modes
- Indication of the light duration and battery level
- Ring and spring clip in the back
- Neodymium magnet optional
- Photoluminescent bezel optional



2 versions: L-90 (3x alkaline AA)

L-90R (Li-ion battery)

ATEX II 1G Ex ia op is IIC T4 Ga
 GAS ZONE 0 | 1 | 2

Ingress protection: IP67

Weight: L-90: 340 g (alkalines included)

L-90R: 290 g (battery included)

Measures (LxWxH): 73x71x158 mm

Autonomy: Normal mode: L-90: > 10 h / L-90R: 4 h

Saving mode: L-90: > 20 h / L-90R: 18 h

Torch body material: Thermoplastic resine with high resistance to the impacts, extreme temperatures and corrosive substances

Lighting source: L-90 High: 250 lm / Saving mode: 80 lm

L-90R High: 280 lm / Saving mode: 80 lm

On/Off button: Made of soft touch material, it's placed on the top to guarantee easy finding and pushing with gloves

Battery level: the button lights up (green or red) to inform about the battery capacity

Chargers for 1, 2, 3 or 5 torches

Step
 Lighting
 System

BOOSTER



www.fsesafe.com / www.fse-exdigital.com